Technical Data Sheet



Nichigo G-TapeTM 2010BK

Seaming, Marking, Protection and Packaging Tape

1. Product Description

Nichigo G-TapeTM 2010BK is single sided tape built with a HDPE cloth laminated with LDPE and propriatery acrylic adhesive. G-Tape 2010BK provides user friendly handling and superior physical properties compared with conventional adhesive tapes.

2. Structure

Laminated Polyethylene Cloth (Black)
Acrylic Adhesion

3. Key Features and benefits

- 3-1) Easy to tear by hands straight no cutting tool is required
- 3-2) Scrap-less ("face to face contact on adhesive sides" comes off clean)
- 3-3) Residue free removal from plastics, metals, painted surfaces, and ceramics,
- 3-4) Repositionable no wrinkles
- 3-5) High UV resistance

4. Physical Properties

- 4-1) Waterproof 4-2) High weather resistant 4-3) Wide application temperature $-4 \sim 190$ ° F
- 4-4) High dimensional stability 4-5) High chemical and solvent resistance

<u>5. Adhesion Properties</u> (*typical values, not for specification or guarantee purpose)

Content	Unit	Value
Total Thickness	Mil	6.3
Adhesive Strength	Oz/in	44
Holding Power	mm gap	0.1
Tensile Strength	Lb/in	32
Elongation at break	%	15

Testing Method JIS Z0237

6. Applications

- 6-1) Masking for painting, stucco, mortar, and sealant indoor and outdoor
- 6-2) Seaming for house wrap, insulation board, floor protection sheet
- 6-3) Residue free floor marking tape
- 6-4) Surface and edge protection for metals, wood, plastic, stones, ceramics, glass, painted surfaces
- 6-5) Quick repair
- 6-6) Packaging
- 6-7) A convenient tape for an emergency kid, outdoor activities, construction fields, home and school.

7. Cautions and How to Use

- 7-1) Avoid prolonged contact with skin. May cause irritation.
- 7-2) Do not use as an electrical insulation tape.
- 7-3) Do not use on PVC, natural marble stones, unfinished wood, decorated wooden boards, uncured coating or delicate surfaces. Test before use. This tape may damage the surfaces and/or leave residue.
- 7-4) Use only clean, dry surfaces.
- 7-5) Store in a dark, dry, cool place.

8. Limitation of Remedy and Liability

Replace of the product or refund of the purchase price, at the purchase price, at our option, shall be your exclusive remedy. We will not be liable for any loss or damage arising from this product, whether direct, indirect, special, incidental, or consequential.



3930 Ventura Drive Suite 355, Arlington Heights, IL 60004

(Tel) 847-255-1211 Ex 135 (Cell) 713-416-9834 sakaguchi.yasuo@me.nichigo.co.jp

Or (Cell) 630-360-4560 mike.coffman@ma.nichigo.co.jp